Pressure Relief Valve 579802 (46503-00)



LabVolt Series

Datasheet



Table of Contents

General Description	·	3
Specifications	5	3

© Festo Didactic 2

General Description

The pressure relief valve or safety relief valve opens at a safely rated fluid-pressure level. The device also helps to ensure that the system fluid-pressure ratings are not exceeded. A discharge line (left- and right-side modules included) safely redirects the fluid as it is expelled from a relief valve. Although the training system operates safely without pressure relief valves, they are useful to demonstrate the normal safety precautions necessary in actual system installations.

Specifications

Parameter	Value
Inlet and Outlet Diameter	1.3 cm (0.5 in)
Rating	
Pressure	10.34 bar (150 psig)
Temperature	98.9°C (210°F)
Physical Characteristics	
Dimensions (H x W x D)	79.7 x 15.3 x 7 cm (31.38 x 6.02 x 2.76 in)
Net Weight	0.318 kg (0.7 lb)

Reflecting the commitment of Festo Didactic to high quality standards in product, design, development, production, installation, and service, our manufacturing and distribution facility has received the ISO 9001 certification.

Festo Didactic reserves the right to make product improvements at any time and without notice and is not responsible for typographical errors. Festo Didactic recognizes all product names used herein as trademarks or registered trademarks of their respective holders. © Festo Didactic Inc. 2024. All rights reserved.

Festo Didactic SE

Rechbergstrasse 3 73770 Denkendorf Germany

P. +49(0)711/3467-0 F. +49(0)711/347-54-88500

Festo Didactic Inc.

607 Industrial Way West Eatontown, NJ 07724 United States

P. +1-732-938-2000 F. +1-732-774-8573

Festo Didactic Ltée/Ltd

675 rue du Carbone Québec QC G2N 2K7 Canada

P. +1-418-849-1000 F. +1-418-849-1666

www.labvolt.com

www.festo-didactic.com

© Festo Didactic 4