Plate Heat Exchanger 579804 (46505-00)



LabVolt Series

Datasheet



* The product images shown in this document are for illustration purposes; actual products may vary. Please refer to the Specifications section of each product/item for all details. Festo Didactic reserves the right to change product images and specifications at any time without notice.

Festo Didactic en 11/2024

Table of Contents

General Description	3
Specifications	3

© Festo Didactic 2

General Description

The plate heat exchanger, an external device, is a copper, brazed-plate type of heat exchanger that transfers thermal energy through a fluid containment wall.

Specifications

Parameter	Value
Туре	Copper, brazed flat plate
Inlet and Outlet Diameter	1.3 cm (0.5 in)
Number of Ports	1 input, 1 output (cold side); 1 input, 1 output (hot side)
Number of Plates	10
Thermal Transfer Area	0.121 m ² (1.3 ft ²)
Solar/Transfer Fluid Volume	114 mL (0.03 US gal) on each side
Maximal Heat Capacity	13.2 kW (45 000 BTU/hr)
Plate Dimensions	20.32 x 8.26 cm (8 x 3.25 in)
Physical Characteristics	
Dimensions (H x W x D)	22.3 x 12 x 10.5 cm (8.78 x 4.7 x 4.13 in)
Net Weight	1.66 kg (3.66 lb)

© Festo Didactic

Reflecting the commitment of Festo Didactic to high quality standards in product, design, development, production, installation, and service, our manufacturing and distribution facility has received the ISO 9001 certification.

Festo Didactic reserves the right to make product improvements at any time and without notice and is not responsible for typographical errors. Festo Didactic recognizes all product names used herein as trademarks or registered trademarks of their respective holders. © Festo Didactic Inc. 2024. All rights reserved.

Festo Didactic SE

Rechbergstrasse 3 73770 Denkendorf Germany

P. +49(0)711/3467-0 F. +49(0)711/347-54-88500

Festo Didactic Inc.

607 Industrial Way West Eatontown, NJ 07724 United States

P. +1-732-938-2000 F. +1-732-774-8573

Festo Didactic Ltée/Ltd

675 rue du Carbone Québec QC G2N 2K7 Canada

P. +1-418-849-1000 F. +1-418-849-1666

www.labvolt.com

www.festo-didactic.com

© Festo Didactic 4