Flow Control Valve 582367 (6421-00)



LabVolt Series

Datasheet



^{*} The product images shown in this document are for illustration purposes; actual products may vary. Please refer to the Specifications section of each product/item for all details. Festo Didactic reserves the right to change product images and specifications at any time without notice.

Table of Contents

General Descri _l	ption	3
Specifications		3

© Festo Didactic 2

General Description

The Flow Control Valve consists of a needle valve and a reverse free-flow check valve connected in parallel. It restricts the flow rate in one direction, while allowing the air to flow freely in the other direction.

Specifications

Parameter	Value
Minimum Operating Pressure	105 kPa (15 psi)
Maximum Operating Pressure	700 kPa (100 psi)
Physical Characteristics	
Dimensions (H x W x D)	89 x 127 x 76 mm (3.5 x 5.0 x 3.5 in)
Net Weight	0.3 kg (0.7 lb)

Reflecting the commitment of Festo Didactic to high quality standards in product, design, development, production, installation, and service, our manufacturing and distribution facility has received the ISO 9001 certification.

Festo Didactic reserves the right to make product improvements at any time and without notice and is not responsible for typographical errors. Festo Didactic recognizes all product names used herein as trademarks or registered trademarks of their respective holders. © Festo Didactic Inc. 2025. All rights reserved.

Festo Didactic SE

Rechbergstrasse 3 73770 Denkendorf Germany

P. +49(0)711/3467-0 F. +49(0)711/347-54-88500

Festo Didactic Inc.

607 Industrial Way West Eatontown, NJ 07724 United States

P. +1-732-938-2000 F. +1-732-774-8573

Festo Didactic Ltée/Ltd

675 rue du Carbone Québec QC G2N 2K7 Canada

P. +1-418-849-1000 F. +1-418-849-1666

www.labvolt.com

www.festo-didactic.com

© Festo Didactic 4