Interconnection Module 586176 (3787-10)



LabVolt Series

Datasheet



Table of Contents

General Description_	·	3
Specifications		3

© Festo Didactic 2

General Description

The Interconnection Module consists of three sets of twelve 4 mm safety banana jacks and three multiple-contact connectors mounted on the front panel of a full-height EMS module. Three interconnection cables, supplied with the module, are used to connect the banana jacks on the Interconnection Module to the banana jacks on the interconnection panel of the Protective Relaying Control Station, Model 3806, via the multiple contact connectors. This provides an efficient means of interconnecting the electrical power system (EMS system) to the relays installed in the protective relaying control station.

Specifications

Parameter	Value
Ratings	
Voltage	450 V
Current	5 A
Physical Characteristics	
Dimensions (H x W x D)	308 x 287 x 440 mm (12.1 x 11.5 x 17.3 in)
Net Weight	6.9 kg (15.2 lb)

Reflecting the commitment of Festo Didactic to high quality standards in product, design, development, production, installation, and service, our manufacturing and distribution facility has received the ISO 9001 certification.

Festo Didactic reserves the right to make product improvements at any time and without notice and is not responsible for typographical errors. Festo Didactic recognizes all product names used herein as trademarks or registered trademarks of their respective holders. © Festo Didactic Inc. 2025. All rights reserved.

Festo Didactic SE

Rechbergstrasse 3 73770 Denkendorf Germany

P. +49(0)711/3467-0 F. +49(0)711/347-54-88500

Festo Didactic Inc.

607 Industrial Way West Eatontown, NJ 07724 United States

P. +1-732-938-2000 F. +1-732-774-8573

Festo Didactic Ltée/Ltd

675 rue du Carbone Québec QC G2N 2K7 Canada

P. +1-418-849-1000 F. +1-418-849-1666

www.labvolt.com

www.festo-didactic.com

© Festo Didactic 4