Buzzer 587173 (9124-00)





Datasheet



Festo Didactic en 04/2025

* The product images shown in this document are for illustration purposes; actual products may vary. Please refer to the Specifications section of each product/item for all details. Festo Didactic reserves the right to change product images and specifications at any time without notice.

Table of Contents

General Description______ 3

General Description

The Buzzer is a self-contained, low-voltage, battery-operated device. A buzzing sound is heard when a patch cord is plugged into the two polarized jacks, thus completing the external circuit.

The test buzzer is an audible signalling device used by electricians to identify wires and terminals that are directly interconnected. It determines whether switch contacts are open or closed, or whether wiring is short circuited. Unlike an ohmmeter, the buzzer will not indicate circuit continuity if any appreciable resistance is present.

Reflecting the commitment of Festo Didactic to high quality standards in product, design, development, production, installation, and service, our manufacturing and distribution facility has received the ISO 9001 certification.

Festo Didactic reserves the right to make product improvements at any time and without notice and is not responsible for typographical errors. Festo Didactic recognizes all product names used herein as trademarks or registered trademarks of their respective holders. © Festo Didactic Inc. 2025. All rights reserved.

Festo Didactic SE

Rechbergstrasse 3 73770 Denkendorf Germany

P. +49(0)711/3467-0 F. +49(0)711/347-54-88500

Festo Didactic Inc.

607 Industrial Way West Eatontown, NJ 07724 United States

P. +1-732-938-2000 F. +1-732-774-8573

Festo Didactic Ltée/Ltd

675 rue du Carbone Québec QC G2N 2K7 Canada

P. +1-418-849-1000 F. +1-418-849-1666

www.labvolt.com

www.festo-didactic.com