Mechanical Interlock 587176 (9125-20)



LabVolt Series

Datasheet



Table of Contents

General Descri	ption	3

© Festo Didactic 2

General Description

The Mechanical Interlock consists of a metal arm hinged at the center to a metal bracket. When mounted between two contactors, the ends of the arm engage each armature. When one contactor closes, its armature rises, pulling the arm up with it and causing the other end of the arm to move down and interfere with the closing of the other contactor.

© Festo Didactic

Reflecting the commitment of Festo Didactic to high quality standards in product, design, development, production, installation, and service, our manufacturing and distribution facility has received the ISO 9001 certification.

Festo Didactic reserves the right to make product improvements at any time and without notice and is not responsible for typographical errors. Festo Didactic recognizes all product names used herein as trademarks or registered trademarks of their respective holders. © Festo Didactic Inc. 2025. All rights reserved.

Festo Didactic SE

Rechbergstrasse 3 73770 Denkendorf Germany

P. +49(0)711/3467-0 F. +49(0)711/347-54-88500

Festo Didactic Inc.

607 Industrial Way West Eatontown, NJ 07724 United States

P. +1-732-938-2000 F. +1-732-774-8573

Festo Didactic Ltée/Ltd

675 rue du Carbone Québec QC G2N 2K7 Canada

P. +1-418-849-1000 F. +1-418-849-1666

www.labvolt.com

www.festo-didactic.com

© Festo Didactic 4