Float Switch 588242 (6570-00)



LabVolt Series

Datasheet



* The product images shown in this document are for illustration purposes; actual products may vary. Please refer to the Specifications section of each product/item for all details. Festo Didactic reserves the right to change product images and specifications at any time without notice.

Festo Didactic en 11/2024

Table of Contents

General Description	3	ì
Specifications		,

General Description

The Float Switch consists of a reed-relay float switch with magnet-equipped float. Its mounting is vertical and inside the level column. The reed contact is hermetically sealed and normally closed, with a positioning range of 25 cm (10 in). The Float Switch operates at atmospheric pressure.

Specifications

Parameter	Value
Туре	Reed-relay, with magnet-equipped float
Mounting	Vertical, inside the level column
Reed Contact	
Туре	Hermetically sealed, normally closed
Positioning Range	25 cm (10 in)
Operating Pressure	Atmospheric pressure

Reflecting the commitment of Festo Didactic to high quality standards in product, design, development, production, installation, and service, our manufacturing and distribution facility has received the ISO 9001 certification.

Festo Didactic reserves the right to make product improvements at any time and without notice and is not responsible for typographical errors. Festo Didactic recognizes all product names used herein as trademarks or registered trademarks of their respective holders. © Festo Didactic Inc. 2024. All rights reserved.

Festo Didactic SE

Rechbergstrasse 3 73770 Denkendorf Germany

P. +49(0)711/3467-0 F. +49(0)711/347-54-88500

Festo Didactic Inc.

607 Industrial Way West Eatontown, NJ 07724 United States

P. +1-732-938-2000 F. +1-732-774-8573

Festo Didactic Ltée/Ltd

675 rue du Carbone Québec QC G2N 2K7 Canada

P. +1-418-849-1000 F. +1-418-849-1666

www.labvolt.com

www.festo-didactic.com