Power Supply (Radar Electronic Warfare) 8095962 (9609-10)



LabVolt Series

Datasheet



Table of Contents

General Description_	3
Specifications	3

© Festo Didactic 2

General Description

The Power Supply can be installed under the surface of the Target Positioning System to provide power to the Radar Jamming Pod Trainer. It provides the same unregulated DC voltages as the Power Supply / Antenna Motor Driver through a multi-pin connector located on its top panel. This connector is identical to the power connector used on several other modules of the system and has the same pin configuration.

Specifications

Parameter	Value
Power Requirement	
Current	1.5 A (for 120 V)
Service Installation	Standard single-phase ac outlet
Unregulated DC Outputs	-25 V typ1.0 A max.; +11 V typ1.5 A max.; +25 V typ1.0 A max.
Line Input Protection	2 A / 1 A circuit breaker
Unregulated DC Output Protection	1.0 A and 1.5 A circuit breaker
Physical Characteristics	
Dimensions (H x W x D)	112 x 330 x 300 mm (4.4 x 13 x 11.8 in)
Net Weight	6.7 kg (14.8 lb)

3 © Festo Didactic

Reflecting the commitment of Festo Didactic to high quality standards in product, design, development, production, installation, and service, our manufacturing and distribution facility has received the ISO 9001 certification.

Festo Didactic reserves the right to make product improvements at any time and without notice and is not responsible for typographical errors. Festo Didactic recognizes all product names used herein as trademarks or registered trademarks of their respective holders. © Festo Didactic Inc. 2024. All rights reserved.

Festo Didactic SE

Rechbergstrasse 3 73770 Denkendorf Germany

P. +49(0)711/3467-0 F. +49(0)711/347-54-88500

Festo Didactic Inc.

607 Industrial Way West Eatontown, NJ 07724 United States

P. +1-732-938-2000 F. +1-732-774-8573

Festo Didactic Ltée/Ltd

675 rue du Carbone Québec QC G2N 2K7 Canada

P. +1-418-849-1000 F. +1-418-849-1666

www.labvolt.com

www.festo-didactic.com

© Festo Didactic 4