Permanent Magnet DC Motor 8114247 (8213-10)



LabVolt Series

Datasheet



^{*} The product images shown in this document are for illustration purposes; actual products may vary. Please refer to the Specifications section of each product/item for all details. Festo Didactic reserves the right to change product images and specifications at any time without notice.

Festo Didactic en 11/2024

Table of Contents

| General Description | _ 3 |
|---------------------|-----|
| Specifications | _ 3 |

© Festo Didactic 2

General Description

The Permanent Magnet DC Motor is a high-speed, brushed dc motor mounted in a full-size EMS module. The magnetic field required for motor operation is produced by powerful permanent magnets mounted on the motor stator. Connections to the motor are made through color-coded safety banana jacks located on the front panel on the module. Power to the motor must be fed by an external dc power source. A toggle switch mounted on the front panel can be used to switch dc power to the motor on and off when the motor is connected to a battery pack. When driven by a prime mover, the Permanent Magnet DC Motor operates as a dc generator.

The front panel of the Permanent Magnet DC Motor module can be opened to install a Timing Belt on the pulley of the motor shaft. This permits mechanical coupling of this motor to the Four-Quadrant Dynamometer/Power Supply. The diameter of the Permanent Magnet DC Motor pulley is smaller (12 teeth) than that of the pulleys of the Four-Quadrant Dynamometer/Power Supply (24 teeth). This difference of pulley ratio (12 to 24) permits adapting the speed (0 4000 r/min) of the Permanent Magnet DC Motor to the speed of the Four-Quadrant Dynamometer/Power Supply (between 0 2000 r/min).

Specifications

| Parameter | Value |
|--------------------------|---|
| Rating | |
| Power | 220 W |
| Voltage | 48 V |
| Current | 5.5 A |
| Speed | 3600 rpm |
| Maximum voltage | 60 V |
| Maximum speed | 4712 rpm |
| Pulley | |
| Number of teeth | 12 |
| Physical Characteristics | |
| Dimensions (H x W x D) | 308 x 291 x 440 mm (2.1 x 11.5 x 17.3 in) |
| Net Weight | 7.6 kg (16.8 lb) |

3 © Festo Didactic

Reflecting the commitment of Festo Didactic to high quality standards in product, design, development, production, installation, and service, our manufacturing and distribution facility has received the ISO 9001 certification.

Festo Didactic reserves the right to make product improvements at any time and without notice and is not responsible for typographical errors. Festo Didactic recognizes all product names used herein as trademarks or registered trademarks of their respective holders. © Festo Didactic Inc. 2024. All rights reserved.

Festo Didactic SE

Rechbergstrasse 3 73770 Denkendorf Germany

P. +49(0)711/3467-0 F. +49(0)711/347-54-88500

Festo Didactic Inc.

607 Industrial Way West Eatontown, NJ 07724 United States

P. +1-732-938-2000 F. +1-732-774-8573

Festo Didactic Ltée/Ltd

675 rue du Carbone Québec QC G2N 2K7 Canada

P. +1-418-849-1000 F. +1-418-849-1666

www.labvolt.com

www.festo-didactic.com

© Festo Didactic 4